

Vollgummi-Bandagen



Serie 79 S

Artikelcode	D mm	W mm	d mm	kg
79 S/160/050/100 A	160	50	100	250
79 S/180/050/120 A	180	50	120	325
79 S/200/050/140 A	200	50	140	350
79 S/200/085/105 A	200	85	105	550
79 S/230/050/170 A	230	50	170	400
79 S/250/050/190 A	250	50	190	450
79 S/250/060/190 A	250	60	190	525
79 S/250/080/170 A	250	80	170	675
79 S/250/075/140 A	250	75	140	625
79 S/250/105/170 A	250	105	170	845
79 S/250/130/140 A	250	130	140	975
79 S/254/102/165 A	254,0 (10")	102,0 (4")	165,0 (6 ½")	850
79 S/270/105/170 A	270	105	170	900
79 S/285/075/220 A	285	75	220	725
79 S/285/100/203 A	285	100	203	960
79 S/300/075/240 A	300	75	240	700
79 S/300/090/203 A	300	90	203	900
79 S/405/065/305 A	405	65	305	900
79 S/405/130/305 A	405	130	305	1.500
79 S/415/075/305 A	415	75	305	1.000
79 S/425/150/305 A	425	150	305	1.910
79 S/457/203/308 A	457,0 (18")	203,0 (8")	308,0 (12 ½")	3.000
79 S/457/229/308 A	457,0 (18")	229,0 (9")	308,0 (12 ½")	3.710
79 S/520/120/370 A	520	120	370	1.775
79 S/550/160/410 A	550	160	410	2.250
79 S/610/150/410 A	610	150	410	2.500
79 S/620/200/410 A	620	200	410	3.785
79 S/660/250/480 A	660	250	480	3.750
79 S/680/150/470 A	680	150	470	2.500
79 S/711/254/559 A	711	254	559	4.375
79 S/1016/305/762 A	1016	305	762	8.760
79 S/1016/406/762 A	1016	406	762	12.420

A = Antriebsradqualität

Vollgummi-Bandagen

Zylindrisch mit Stahlring in Antriebsqualität und Flachprofil. Vollgummi-Bandagen mit Geländeprofil oder nicht kreidend auf Anfrage.

